

Peripheral device reassignment control technique

KR Barbour, HJ Evans - US Patent 3,940,380, 1976 - Google Patents
... kept vice table in addition includes a plurality of locations **track** of by ... of AND
gate 98 in response to the timing **signal** T9 and the **device** table address ...

[Cited by 11](#) - [Related articles](#) - [All 3 versions](#)

... memory partitioned into lines accessible by corresponding I/O devices and a directory to track ...

A Chang, GA Lerom, JO Nicholson, JC O'Quin ... - US Patent 5,418,927, 1995 - Google Patents
... I/O DEVICES AND A DHECTORY TO TRACK THE 5 ... virtual page table before an input- /output
device is allowed ... buffer system; 28 are connected through **signal** line 30 ...

[Cited by 15](#) - [Related articles](#) - [All 2 versions](#)

... and method in a network interface device for storing status information contiguous with a ...

JCJ Kuo, PS Lai, AJ Niu ... - US Patent 6,061,767, 2000 - Google Patents
... the write controller and read controller **devices** be coordinated ... **status** information
65 and the frame **track** field 66 ... the end of frame (RM_ENF) **signal**, the memory ...

[Cited by 6](#) - [Related articles](#) - [All 2 versions](#)

... a network interface device for storing tracking information indicating stored data status ...

JCJ Kuo, AJ Niu, PS Lai ... - US Patent 6,061,768, 2000 - Google Patents
... of a counter value in response to an increment **signal**. ... o Frame **Track**, 66 68 r Frame
Track Figure 4 RM ... for an arrangement in a network interface **device**, where a ...

[Cited by 6](#) - [Related articles](#) - [All 2 versions](#)

Monitoring device for location verification

CK LaDue - US Patent 5,525,969, 1996 - Google Patents
... and systems are used to essentially **track** and verify ... with remote communicators with-
out transmitting a **signal** to a ... the 60 **location** or condition of the **device**. ...

[Cited by 9](#) - [Related articles](#) - [All 2 versions](#)

... and method in a network interface device for storing receiving frame status in a holding ...

JCJ Kuo, AJ Niu, PS Lai ... - US Patent 6,154,796, 2000 - Google Patents
... reads the frame synchronous to the PCI bus clock **signal**. ... the write controller and
read controller **devices** be coordinated ... by the RB_MMU 22c to keep **track** of the ...

[Cited by 6](#) - [Related articles](#) - [All 2 versions](#)

System and method for signaling a device at a remote location over a wireless network

BM Snyder ... - US Patent 5,568,038, 1996 - Google Patents
... the battery, for example, an automobile or **track** alternator ... The homing transmitter
214 is also a conventional **device**, designed to produce a **signal**, radio tone ...

[Cited by 19](#) - [Related articles](#) - [All 4 versions](#)

I/O device reconnection in a multiple-CPU, dynamic path allocation environment

PE Brunello, BF Southerland - US Patent 4,697,232, 1987 - Google Patents
... to a CPU after the for a particular **location** on a data **track** which is ... or suppressible,
may be thought of as a "**device** connect ready **signal**" that alerts ...

[Cited by 7](#) - [Related articles](#) - [All 2 versions](#)

Emergency locator **device** transmitting **location data** by wireless telephone communications

B Tognazzini - US Patent 5,914,675, 1999 - Google Patents

... The GPS receiver 16 may **track** up to 8 ... disclosed embodiment, the emergency signals into digital **signal** samples for transmission by the locator **device** 10 and ...

[Cited by 17](#) - [Related articles](#) - [All 5 versions](#)

... a monitor in each I/O **device** control for generating signals based upon the **device status**

DR Evoy - US Patent 5,628,029, 1997 - Google Patents

... means coupled to said peripheral control means and said 15 logic must **track** the change. ... 2, a distributed I/O **device** monitoring said SMI # **signal** and for ...

[Cited by 6](#) - [Related articles](#) - [All 2 versions](#)

Google

Result Page:

[1](#) [2](#) [3](#) [4](#) [5](#) [6](#) [7](#) [8](#) [9](#) [10](#)

[Next](#)

track device signal status proper loc

Search

[Go to Google Home](#) - [About Google](#) - [About Google Scholar](#)

©2009 Google